

The universal air humidifier UB-12/3.1 is a product of the AIRWIN® brand of BOGA GmbH. It is used for the fully automatic production of aerosol mist from demineralised water according to the ultrasonic principle. Performance of the humidifier is controlled by an external hygrostat ON/OFF signal, MODBUS RTU or by a customer-supplied, continuous control signal.

Specification

- Housing with aerosol exhaust pipes made of demineralised water-resistant stainless steel
- Filtering of the intake air by washable coarse filter
- Two cross flow fans for cooling of electronic components and transport of the aerosol mist through the exhaust pipes
- Central electrical control connection to 15-pole plug
- MODBUS RTU interface designed as D-SUB
- Ultrasonic oscillating circuit with integrated fuse and temperature monitoring of the power transistors
- Stepless power control when operating with analog control signal
- Status messages for humidification and collective fault
- Integrated routines for error detection at water supply and drain
- Redundant level monitoring
- Current measurement of active components
- Electrical power connection 48 V-AC at the built-in socket
- Possibility to connect standard control signals 0-10 VDC, and 4-20 mA
- Possibility to connect a hygrostat - also 2-stage
- Possibility to connect a wired remote control, 2-channel
- Possibility to connect a safety chain
- Solenoid valve combination for water supply and water drainage
- Water-technical connection without tools by means of hose connectors for metric hoses/pipes
- Automatic level control of the water level, dry-running protection, overheat protection, protection against overvoltage peaks, overflow protection, disconnection protection
- **AquaDrain plus:** integrated hygiene management for cyclical flushing of the water inlet pipe and cyclical or permanent emptying of the fluid tank according to pre-set parameters

Technical data

Max. humidification output	6	kg/h
Number of transducers:	12	
Power consumption	450	VA

Dimensions

Installation dimensions of humidifier – height x width x depth	268 x 980 x 368	mm
Aerosol exhaust pipe	Ø 75	mm
Hose water inlet	Ø 6	mm
Hose water overflow/discharge	Ø 12	mm
Weight	25	kg

Conditions of use

Power supply	48 / 50	V / Hz
Conductivity of demineralised water	5...20	µS/cm
Ambient temperature	5...45	°C
Ambient humidity	0...90	% RH
Water temperature	5...40	°C
Water pressure	1...6	bar

Delivery volume

- UB-12/3.1 universal air humidifier
- Installation and operating instructions
- Water filter for hose D/d = 6/4 mm (incl. 100 mm hose)
- Stop cock Ø 6 mm
- Plug 3-pole, 20 A
- D-SUB Connector male, 15-pol, housing

Product specification

Brand	AIRWIN®
Model	UB-12/3.1
Item No.	7900613



Rev 07/2021



The universal air humidifier UB-18/3.1 is a product of the AIRWIN® brand of BOGA GmbH. It is used for the fully automatic production of aerosol mist from demineralised water according to the ultrasonic principle. Performance of the humidifier is controlled by an external hygrostat ON/OFF signal, MODBUS RTU or by a customer-supplied, continuous control signal.

Specification

- Housing with aerosol exhaust pipes made of demineralised water-resistant stainless steel
- Filtering of the intake air by washable coarse filter
- Two cross flow fans for cooling of electronic components and transport of the aerosol mist through the exhaust pipes
- Central electrical control connection to 15-pole plug
- MODBUS RTU interface designed as D-SUB
- Ultrasonic oscillating circuit with integrated fuse and temperature monitoring of the power transistors
- Stepless power control when operating with analog control signal
- Status messages for humidification and collective fault
- Integrated routines for error detection at water supply and drain
- Redundant level monitoring
- Current measurement of active components
- Electrical power connection 48 V-AC at the built-in socket
- Possibility to connect standard control signals 0-10 VDC, and 4-20 mA
- Possibility to connect a hygrostat - also 2-stage
- Possibility to connect a wired remote control, 2-channel
- Possibility to connect a safety chain
- Solenoid valve combination for water supply and water drainage
- Water-technical connection without tools by means of hose connectors for metric hoses/pipes
- Automatic level control of the water level, dry-running protection, overheat protection, protection against overvoltage peaks, overflow protection, disconnection protection
- **AquaDrain plus:** integrated hygiene management for cyclical flushing of the water inlet pipe and cyclical or permanent emptying of the fluid tank according to pre-set parameters

Technical data

Max. humidification output	9	kg/h
Number of transducers:	18	
Power consumption	675	VA

Dimensions

Installation dimensions of humidifier – height x width x depth	268 x 980 x 368	mm
Aerosol exhaust pipe	Ø 75	mm
Hose water inlet	Ø 6	mm
Hose water overflow/discharge	Ø 12	mm
Weight	26	kg

Conditions of use

Power supply	48 / 50	V / Hz
Conductivity of demineralised water	5...20	µS/cm
Ambient temperature	5...45	°C
Ambient humidity	0...90	% RH
Water temperature	5...40	°C
Water pressure	1...6	bar

Delivery volume

- UB-18/3.1 universal air humidifier
- Installation and operating instructions
- Water filter for hose D/d = 6/4 mm (incl. 100 mm hose)
- Stop cock Ø 6 mm
- Plug 3-pole, 20 A
- D-SUB Connector male, 15-pol, housing

Product specification

Brand	AIRWIN®
Model	UB-18/3.1
Item No.	7900619



Rev 07/2021



The universal air humidifier UB-24/3.1 is a product of the AIRWIN® brand of BOGA GmbH. It is used for the fully automatic production of aerosol mist from demineralised water according to the ultrasonic principle. Performance of the humidifier is controlled by an external hygrostat ON/OFF signal, MODBUS RTU or by a customer-supplied, continuous control signal.

Specification

- Housing with aerosol exhaust pipes made of demineralised water-resistant stainless steel
- Filtering of the intake air by washable coarse filter
- Two cross flow fans for cooling of electronic components and transport of the aerosol mist through the exhaust pipes
- Central electrical control connection to 15-pole plug
- MODBUS RTU interface designed as D-SUB
- Ultrasonic oscillating circuit with integrated fuse and temperature monitoring of the power transistors
- Stepless power control when operating with analog control signal
- Status messages for humidification and collective fault
- Integrated routines for error detection at water supply and drain
- Redundant level monitoring
- Current measurement of active components
- Electrical power connection 48 V-AC at the built-in socket
- Possibility to connect standard control signals 0-10 VDC, and 4-20 mA
- Possibility to connect a hygrostat - also 2-stage
- Possibility to connect a wired remote control, 2-channel
- Possibility to connect a safety chain
- Solenoid valve combination for water supply and water drainage
- Water-technical connection without tools by means of hose connectors for metric hoses/pipes
- Automatic level control of the water level, dry-running protection, overheat protection, protection against overvoltage peaks, overflow protection, disconnection protection
- **AquaDrain plus:** integrated hygiene management for cyclical flushing of the water inlet pipe and cyclical or permanent emptying of the fluid tank according to pre-set parameters

Technical data

Max. humidification output	12	kg/h
Number of transducers:	24	
Power consumption	900	VA

Dimensions

Installation dimensions of humidifier – height x width x depth	268 x 980 x 368	mm
Aerosol exhaust pipe	Ø 75	mm
Hose water inlet	Ø 6	mm
Hose water overflow/discharge	Ø 12	mm
Weight	28	kg

Conditions of use

Power supply	48 / 50	V / Hz
Conductivity of demineralised water	5...20	µS/cm
Ambient temperature	5...45	°C
Ambient humidity	0...90	% RH
Water temperature	5...40	°C
Water pressure	1...6	bar

Delivery volume

- UB-24/3.1 universal air humidifier
- Installation and operating instructions
- Water filter for hose D/d = 6/4 mm (incl. 100 mm hose)
- Stop cock Ø 6 mm
- Plug 3-pole, 20 A
- D-SUB Connector male, 15-pol, housing

Product specification

Brand	AIRWIN®
Model	UB-24/3.1
Item No.	7900626



Rev 07/2021

